

The Philips logo is displayed in blue capital letters on a white background within a rounded square graphic.The text "Service update" is written in white on a green background, which is part of the rounded square graphic.

Improved lead times to meet your needs

We are pleased to announce improvements and lead time commitments for Philips Lumec outdoor roadway product families.

Committed to service

Based on market feedback and our competitive landscape, we have significantly invested in improving the lead times on our most popular outdoor roadway luminaire families. And we're just getting started. Look for additional Roadway family lead times to be improved in the future.

We understand products and pricing are only a part of the winning combination. We are committed to giving our customers confidence in our delivery as well. For larger orders we always recommend that you work closely with our Agency Project Managers to help forecast larger opportunities and shipping requirements over a longer period of time.

How it works

1. Orders will be dated appropriately based on the specific configuration once orders are received and accepted.
2. Quantity limit applies based on the family and configuration (see notes). If quantity exceeds these numbers, the factory will contact you to negotiate timing.
3. Contact quotations if lead times are required prior to ordering.
4. Extended lead times may apply to specialized options (as noted in the ordering guides on the following pages).

See the following pages for specific details on the families and configurations.

The following families now have improved and committed lead times for most configurations

Roadway



Philips Lumec StreetView LED cobra head



- Eleven lumen packages with a single housing size providing 2,164 to 17,248 lumens
- Type II, III, and V optical distributions available
- Tool-less access to driver
- Dimming driver (DMG) and Receptacle (RC) Standard
- DLC Qualified and 10 yr limited warranty

Two week lead time applies to the configurations highlighted in green. Four week lead time applies to the configurations highlighted in orange. Six week lead time applies to the configurations highlighted in blue. Extended lead times may apply to specialized options noted in red. Quantities vary depending on the specific configuration chosen.

Ordering guide

example: SVM-90W48LED4K-G2-LE3-UNIV-DMG-RC-HS-GY3

Luminaire	LED Module	Optical System	Voltage	Driver and Dimming	Twist-Lock Receptacle	Surge Protection	Luminaire Accessories	Finish
SVM					RC			GY3
SVM StreetView Medium	16W16LED4K-G2⁴ (order qty 100 max) or 22W16LED4K-G2⁴ (order qty 100 max) or 24W16LED4K-G2⁴ (order qty 100 max) or 30W16LED4K-G2⁴ (order qty 100 max) or 32W32LED4K-G2 (order qty 100 max) or 48W32LED4K-G2 (order qty 25 max) or 60W32LED4K-G2 (order qty 100 max) or 48W48LED4K-G2 (order qty 100 max) or 72W48LED4K-G2 (order qty 250 max) or 90W48LED4K-G2 (order qty 250 max) or 140W48LED4K-G2^{2,4} (order qty 100 max)	LE2 Type II (order qty 250 max) LE3 Type III (order qty 250 max) LE5 Type V (order qty 100 max)	UNIV 120-277VAC: 16 LED 32 LED 48 LED 140W 48 LED (order qty 250 max) HVU 347-480VAC: 32 LED 48 LED (order qty 25 max)	<i>Standard</i> DMG^{1,5} Dimmable 0-10V driver (order qty 250 max) <i>Optional</i> AMPD^{2,4,5} Amplight Dimming (not available for 140W48LED) Dynadimmer Economy Profile CDMGE25^{2,4,5} (qty 250 max) (qty 100 for 16W to 30W items) CDMGE50^{2,4,5} (qty 250 max) CDMGE75^{2,4,5} (qty 250 max) Median Profile CDMGM25^{2,4,5} (qty 250 max) CDMGM50^{2,4,5} (qty 250 max) CDMGM75^{2,4,5} (qty 250 max) Safety Profile CDMGS25^{2,4,5} (qty 250 max) CDMGS50^{2,4,5} (qty 250 max) CDMGS75^{2,4,5} (qty 250 max) DALI^{2,4,5} Digitally Addressable Lighting Interface DMG-AST^{*2,4} Adjustable Startup Time DMG-CLO^{*2,4,5} Constant Light Output DMG-OTL^{*2,4} Over The Life	<i>Standard</i> RC^{1,3} Receptacle for twist-lock photo cell or shorting cap	<i>Standard</i> SP1 10kV / 10kA (qty 250 max) <i>Optional</i> SP2⁶ 20kV / 20kA (qty 100 max)	HS House side shield, 1 per 16 LED light engine (order qty 250 max) PH8^{3,4} Twist-lock Photoelectric Cell, UNIV (120-277VAC) (order qty 250 max) PH8/347³ (not available for 140W48LED) Twist-lock Photoelectric Cell, HVU (347VAC) (order qty 25 max) PH8/480³ (not available for 140W48LED) Twist-lock Photoelectric Cell, HVU (480VAC) (order qty 25 max) PH8XL^{3,4} Twist-lock Photoelectric Cell, extended life, UNIV (120-277VAC) (order qty 250 max) PH9³ Shorting cap (order qty 250 max)	GY3 Grey finish

1. Please note these integrated features come standard with StreetView luminaires.
2. Denotes programmable driver option. Not available with HVU (347-480VAC).
Not available with 1050mA version (140W48LED).
3. Use of photoelectric cell or shorting cap is required to ensure proper illumination.
4. Not available with HVU (347-480volt).
5. Dimming choices: Select either DMG or AMPD or one of the CDMG options or DALI.
6. When SP2 option is selected you will get SP2 instead of standard SP1.



Philips Lumec RoadStar LED architectural roadway

- Up to 9 lumen packages in 2 different housing sizes delivering 3,033 - 32,924 lumens
- Seven different optical distributions, Type 2S, 2M, 3S, 3M, 3W, 4, and 5
- Warm White (3000K) and Neutral White (4000K) color temps available
- Dimming driver (DMG) and receptacle (RCD) standard
- DLC listed with limited 10 yr warranty

Four week lead time applies to the configurations highlighted in orange. Six week lead time applies to the configurations highlighted in blue. Extended lead times may apply to specialized options noted in red.

Ordering guide

example: GPLS-48L700NW-G2-R3M-UNV-DMG-HS-RCD-PH8-WH

Luminaire	Lamp or LED Module	Board generation	Optical System	Ballast	Driver Options	Luminaire Options	Luminaire Accessories	Finish	
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	
GPLS RoadStar Small	16L530NW ³ 16L530WW 16L700NW ³ 16L700WW 16L1050NW ³ 16L1050WW 32L530NW ³ 32L530WW 32L700NW ³ 32L700WW 32L1050NW ³ 32L1050WW 48L530NW ³ 48L530WW 48L700NW ³ 48L700WW 48L1050NW ⁴ 48L1050WW	G2 Generation 2	4 ¹ 5 ³ R2M ³ R2S ¹ R3M ³ R3S ¹ R3W ¹	UNV ³ HVU ¹	DMG ³ (Std. always included) AMPD AST ³ DALI ³ CLO ³ CDMGE25 ³ CDMGE50 ³ CDMGE75 ³ CDMGM25 ³ CDMGM50 ³ CDMGM75 ³ CDMGS25 ³ CDMGS50 ³ CDMGS75 ³	RCD ³ (std, always included) SP1 ³ (std. Always Inc.) HS ³ RCD7 ³ SP2 ³ Note on option: Same parts as SVM and all are at 4W or better in SVM CSO	PH8 ³ PH8/347 ³ PH8/480 ³ PH9 ³ PHXL ³	BK BR GY3 WH Other std color	
GPLM RoadStar Medium	64L530NW ³ 64L530WW 64L700NW ³ 64L700WW 64L1050NW ¹ 64L1050WW 80L530NW ³ 80L530WW 80L700NW ³ 80L700WW 80L1050NW ² 80L1050WW 96L530NW ³ 96L530WW 96L700NW ³ 96L700WW 96L1050NW ² 96L1050WW								

1. Order quantity of 25 maximum.
2. Order quantity of 25 maximum.
O.D of 15 for this driver, until integration to SVM.
3. Order quantity of 50 maximum.
4. Order quantity of 50 maximum.
O.D of 25 for this driver, until integration to SVM.

